



<b>Brand</b>	DAYTON	<b>Thermal Protection</b>	None
<b>Mfr. Model #</b>	3KX01	<b>Rotation</b>	CW/CCW
<b>Ship Weight (lbs.)</b>	89.9	<b>Insulation Class</b>	F
<b>Item</b>	Energy Efficient Motor	<b>Ambient (C)</b>	40
<b>Motor Type</b>	3 Phase	<b>Overall Length (In.)</b>	15.75
<b>HP</b>	3	<b>Shaft Dia. (In.)</b>	1-1/8
<b>Nameplate RPM</b>	1740	<b>Shaft Length (In.)</b>	2.75
<b>Voltage</b>	208-230/460	<b>Phase</b>	3
<b>NEMA/IEC Frame</b>	182T	<b>Agency Compliance</b>	UL Recognized (E104590), CSA Certified (LR38324)
<b>Enclosure</b>	Totally Enclosed Fan-Cooled		
<b>Hz</b>	60		
<b>Full Load Amps</b>	8.9-8/4.0		
<b>Duty</b>	Inverter		
<b>Service Factor</b>	1.15		
<b>Normal Efficiency</b>	87.5		
<b>Mounting</b>	Base		
<b>Bearings</b>	Double Shielded Ball		